

Model		IT-G600-C21-11	IT-G600-WC21-11	IT-G650-C21-11	IT-G650-WC21-11
CPU		Qualcomm SDA/SDM660 (Octa Core 2,2 GHz)			
OS		Android 11, Android Enterprise Recommended			
Memory	RAM	4 GB			
	FROM	64 GB			
Display	Screen Size	4.7 inch, HD (1280 x 720)		5.5 inch, HD+ (1440 x 720)	
	Touch panel	Capacitive Multi-Touch (Dragontrail Pro®)			
Input	Scanner	CMOS Imager unit angle by 25° with Laser Aimer			
	Camera	13 megapixel, Auto focus, LED Flash			
	Key	Power, Volume up / down			
		10 keys (alpha numeric), Function (F1 to F4), Trigger (Center/R/L)		Function (F1 to F4), Trigger (R/L)	
Reset Switch	Hardware Reset				
Sensors		Acceleration, Light Ambient, Proximity, Gyroscope, Geomagnetic (compass) sensor			
Wireless Communication	Bluetooth®	Ver. 5.0 EDR/LE			
	WLAN	IEEE802.11a/b/g/n/ac, IEEE802.11d, WPA2/WPA3(Personal, Enterprise) support			
	WWAN	-	Yes	-	Yes
		LTE, WCDMA Band 1/6/8 (3G Voice communication complied), GSM 900 / GSM 1800			
	GPS	GPS, GLONASS, Michibiki (QZSS/L1C)			
RFID/NFC		ISO14443Type A/B/FeliCa (R), ISO15693, Output Power over 3.5 A/m			
USB		USB 2.0 (Host/Client), USB Type-C (Power supply over 2,000 mA)			
Charging station port		USB 2.0			
SD card slot		microSD (SDXC)			
SIM card slot		-	nano SIM	-	nano SIM
Extention port (for Local Development)		(RFID/NFC, Legic Reader solutions)			
Battery	Main Power	Lithium-ion battery, Approx. 20 hours (JEITA G-mode)			
	Capacity	Changeable Lithium-ion battery with 3,000 mAh			
	Backup Time	RAM Backup: over 4 minutes			
RTC Backup: over 72 hours					
External Dimensions (W x D x H)		approx. 75 x 180 x 18 mm		approx. 78 x 180 x 18 mm	
Weight		approx. 300 g (including battery)		approx. 310 g (including battery)	
Durability	Dust / Water proof	IP67			
	Drop Durability	1.8 m onto concrete		1.5 m onto concrete	
	Temparature	Operation -20 to 50 °C / Non-operation -20 to 60 °C			
	Humidity	Operation 30 to 80 % RH / Non-operation 5 to 90 % RH			

Google, Android, Google Maps, Google Drive and other marks are trademarks of Google LLC. MIFARE is a registered trademark of the NXP B.V. FeliCa is a registered trademark of the Sony Corporation. The Bluetooth® trademark is owned by Bluetooth SIG, Inc., USA, and licensed to CASIO Computer Co., Ltd. Other product- and company names are either trademarks or registered trademarks of the respective owners. The design and specifications may vary without notice. The color display of pictures may vary from the actual colours. Screen images are simulated representations. The specifications in the table above were provided in April 2022.

CASIO grants a warranty period of 12 months on all CASIO System products (cash registers and handy terminals).

### Casio Europe GmbH

Casio-Platz 1  
22848 Norderstedt, Germany  
solutions@casio.de  
+49 (0)40 528 65-407  
www.casio-solutions.com



Model		IT-G600-C21	IT-G600-WC21	IT-G650-C21	IT-G650-WC21
CPU		Qualcomm SDA/SDM660 (Octa Core 2,2 GHz)			
OS		Android 9, Android Enterprise Recommended Upgrading Android 11 is available			
Memory	RAM	4 GB			
	FROM	64 GB			
Display	Screen Size	4.7 inch, HD (1280 x 720)		5.5 inch, HD+ (1440 x 720)	
	Touch panel	Capacitive Multi-Touch (Dragontrail Pro®)			
Input	Scanner	CMOS Imager unit angle by 25° with Laser Aimer			
	Camera	13 megapixel, Auto focus, LED Flash			
	Key	Power, Volume up / down			
		10 keys (alpha numeric), Function (F1 to F4), Trigger (Center/R/L)		Function (F1 to F4), Trigger (R/L)	
	Reset Switch	Hardware Reset			
Sensors		Acceleration, Light Ambient, Proximity, Gyroscope, Geomagnetic (compass) sensor			
Wireless Communication	Bluetooth®	Ver. 5.0 EDR/LE			
	WLAN	IEEE802.11a/b/g/n/ac, IEEE802.11d, WPA2 support			
	WWAN	-	Yes	-	Yes
		LTE, WCDMA Band 1/6/8 (3G Voice communication complied), GSM 900 / GSM 1800			
	GPS	GPS, GLONASS, Michibiki (QZSS/L1C)			
RFID/NFC		ISO14443Type A/B/FeliCa (R), ISO15693, Output Power over 3.5 A/m			
USB		USB 2.0 (Host/Client), USB Type-C (Power supply over 2,000 mA)			
Charging station port		USB 2.0			
SD card slot		microSD (SDXC)			
SIM card slot		-	nano SIM	-	nano SIM
Extention port (for Local Development)		(RFID/NFC, Legic Reader solutions)			
Battery	Main Power	Lithium-ion battery, Approx. 20 hours (JEITA G-mode)			
	Capacity	Changeable Lithium-ion battery with 3,000 mAh			
	Backup Time	RAM Backup: over 4 minutes			
RTC Backup: over 72 hours					
External Dimensions (W x D x H)		approx. 75 x 180 x 18 mm		approx. 78 x 180 x 18 mm	
Weight		approx. 300 g (including battery)		approx. 310 g (including battery)	
Durability	Dust / Water proof	IP67			
	Drop Durability	1.8 m onto concrete		1.5 m onto concrete	
	Temparature	Operation -20 to 50 °C / Non-operation -20 to 60 °C			
	Humidity	Operation 30 to 80 % RH / Non-operation 5 to 90 % RH			

Google, Android, Google Maps, Google Drive and other marks are trademarks of Google LLC. MIFARE is a registered trademark of the NXP B.V. FeliCa is a registered trademark of the Sony Corporation. The Bluetooth® trademark is owned by Bluetooth SIG, Inc., USA, and licensed to CASIO Computer Co., Ltd. Other product- and company names are either trademarks or registered trademarks of the respective owners. The design and specifications may vary without notice. The color display of pictures may vary from the actual colours. Screen images are simulated representations. The specifications in the table above were provided in April 2022.

CASIO grants a warranty period of 12 months on all CASIO System products (cash registers and handy terminals).

**Casio Europe GmbH**  
 Casio-Platz 1  
 22848 Norderstedt, Germany  
 solutions@casio.de  
 +49 (0)40 528 65-407  
 www.casio-solutions.com

