



## Rugged, compact and portable 2" receipt printer

RJ-2030 / RJ-2050 / RJ-2140 / RJ-2150 Data Sheet

## 2" portable receipt and label printer

With its advanced connectivity options, RJ-2 printers are the ideal mobile printer for printing labels, receipts, tickets and other documentation.

The RJ mobile printer integrates into your existing system thanks to Wi-Fi, Bluetooth and USB connectivity.

### Key features:

- Durable with IP54 rating and drop tested up to 2.5m
- Compatible with a wide range of devices and operating systems, including iOS and Android
- Easy to use with mono LCD and three flat membrane keys
- Simple integration into existing applications with free Software Development Kits (SDKs)
- Customisable with power options including rechargeable batteries, AC adaptor, vehicle power kits and linkable battery chargers



## General

<b>Carton contents</b>	Belt Clip Li-ion battery Documentation
<b>Language support</b>	English, French, Dutch, German, Italian, Spanish

## Dimensions and weights

<b>Without carton</b>	<b>RJ-2030 / RJ-2050:</b> 122(w) x 100(d) x 57(h)   465g
	<b>RJ-2140 / RJ-2150:</b> 151(w) x 100(d) x 73(h)   545g

## Built in features

<b>Printing Method</b>	Direct Thermal
<b>Print Resolution</b>	203dpi
<b>Print Speed</b>	Maximum 6ips (152mm/sec) (Under Brother standard environment)
<b>Maximum Print Width</b>	54mm <b>RJ-2140 / RJ-2150:</b> 51mm (labels)
<b>Minimum print length</b>	12.7mm
<b>Maximum print length</b>	1m
<b>LCD</b>	Backlit monochrome LCD
<b>Interfaces</b>	<b>RJ-2030 / RJ-2050 / RJ-2150:</b> USB Ver.2.0 (Full Speed) (Type B) Bluetooth Version.2.1
	<b>RJ-2050 / RJ-2140 / RJ-2150:</b> Wireless LAN 802.11 b/g/n supporting (supporting AirPrint® from iOS® devices)
<b>Bluetooth Profile</b>	<b>RJ-2030:</b> Classic; SPP, OPP, BIP, HCRP
	<b>RJ-2050 / RJ-2150:</b> Classic; SPP, OPP, BIP, HCRP, iAP supported
<b>WLAN Security</b>	<b>RJ-2050 / RJ-2140 / RJ-2150:</b> Authentic method (encryption scheme) <b>AdHoc mode</b> -Open system(None/WEP) Authentic method (encryption scheme) <b>Infrastructure mode</b> -Open system(None/WEP64/WEP128) -Common key authentication (WEP) WPA/WPA2-PSK (TKIP+AES) • LEAP (CKIP) • EAP-FAST (TKIP/AES) • PEAP (TKIP/AES) • EAP-TLS (TKIP/AES) • EAP-TTLS (TKIP/AES) <b>Wireless direct mode</b> -WPA2-PSK (AES)

<b>Operating system support</b>	Microsoft® Windows Vista® / Windows® 7 / Windows® 8 / Windows® 8.1 / Windows® 10 Microsoft® Windows Server® 2008 / 2008 R2 / 2012 / 2012 R2 / 2016 / 2019  Linux
<b>Mobile OS Support</b>	Android 4.0.3 or later iOS® 6 or later Requires 3 <sup>rd</sup> party app development using Brother SDK, further information available at <a href="http://www.brother.co.jp/eng/dev/">www.brother.co.jp/eng/dev/</a>
<b>Printer commands</b>	ZPLII emulation CPCL emulation ESC/P P-touch Template Raster
<b>RAM</b>	32MB
<b>Flash</b>	32MB (12MB available for template upload)
<b>Internal fonts &amp; sizes</b>	<ESC/P commands> Bitmap fonts: Gothic, Letter Gothic Bold, Helsinki Font sizes: 16, 24, 32 dots Outline fonts: Gothic, Letter Gothic Bold, Helsinki Font sizes: 400 dots (maximum) <P-touch Template commands> Outline fonts: Gothic, Letter Gothic Bold, Helsinki Font sizes: 400dots (maximum)

## Environmental

<b>Drop protection</b>	2.5 metres
<b>Sealing</b>	IP54
<b>Operating temperature</b>	Operating: -10C to +50C / Charging: 0C to +40C
<b>Operating humidity</b>	10%-90% / Maximum web bulb: +27C (no condensation)
<b>Storage temperature</b>	-20C to +60C
<b>Storage humidity</b>	10% to 90% (+45C)

## Supplies

	RD-R03E5 (Receipt – 58mm x 12m )
<b>RD roll type</b>	<b>RJ-2140 / RJ-2150:</b> RD-Q04E1 (450 Labels – 51mm x 26mm)

## Optional accessories

<b>Battery</b>	PA-BT-003 Rechargeable Li-ion (7.2V)
<b>Battery Charger</b>	PA-BC-002 (up to 4 can be connected using one AC adaptor)
<b>AC adaptor</b>	PA-AD-600A 100/240V AC (50/60Hz) to 15V DC (only for charging)
<b>Car adaptor</b>	PA-CD-600CG Cigar lighter plug  PA-CD-600WR Permanently wired 12V DC (only for charging)
<b>Shoulder strap</b>	PA-SS-4000

*All specifications are correct at the time of printing and are subject to change without notice. Brother and the brother logo are both trademarks of Brother Industries, Ltd., registered in Japan and certain other countries. Any trade names, logos and product names of other companies appearing are trade names or trademarks of those respective companies.*

*BIE Product Planning: Last updated 17/12/2020*



brother

No. 0792

**Parking Violation**

This vehicle is improperly parked.  
Reason for Violation:

- Vehicle has no valid parking permit
- Parked in no parking zone
- Parked in Blue line
- Parked in Disabled space
- Parked in Reserved space

# Rugged mobile printing, whatever the conditions

RJ-4230B/RJ-4250WB Data Sheet



## The RJ-4200 Series

The rechargeable RJ-4200 printers are an extra tough, super-fast printing solution designed with busy field workers in mind.

Bluetooth gives you extra connectivity, while being able to print receipts, quotes, invoices and labels on the spot will save valuable time for you and your customers.

### Key Features:

- Fast print speeds of 127mm/sec (5ips)
- Portable & robust design
- Multiple connectivity options, including Bluetooth v4.2 and Wireless LAN 802.11 a/b/g/n
- Ready to integrate with iOS® & Android apps
- Mono backlit LCD display
- Compatible with Windows®



## General

<b>Carton contents</b>	Belt Clip Adjuster guide locks Documentation
<b>Language support</b>	Dansk, Deutsch, English, Español, Français, Italian, Nederlands, Norsk, Português, Suomi, Svenska

## Dimensions & Weights

<b>Without carton</b>	153(w) x 159(d) x 68(h)   850g
-----------------------	--------------------------------

## Built In Features

<b>Printing method</b>	Direct Thermal
<b>Print resolution</b>	203dpi
<b>Print speed</b>	Maximum 5ips (127mm/sec) (*under Brother standard environment)
<b>Maximum print width</b>	104mm
<b>Minimum print length</b>	12.7mm
<b>Maximum print length</b>	3000mm
<b>LCD</b>	Backlit monochrome LCD
<b>Number of labels per battery charge</b>	Li-ion battery: approx. 10,000 labels (continuous print) (*under Brother standard environment)
<b>Interfaces</b>	USB Ver.2.0 (Full Speed) (mini-B). Bluetooth Version.4.2 supporting Low Energy NFC (Passive) Wireless LAN 802.11a/b/g/n supporting 2.4GHz and 5GHz^ (supporting Airprint® from iOS® devices)
<b>Bluetooth Profile</b>	Classic; SPP, OPP, HCRP, iAP supported Low Energy GATT
<b>WLAN Security</b>	<b>RJ-4250WB only:</b> Authentic method (encryption scheme)  <b>Infrastructure mode:</b> Open system(None/WEP64/WEP128) Common key authentication (WEP) WPA/WPA2-PSK (TKIP+AES) • EAP-FAST (TKIP/AES) • PEAP (TKIP/AES) • EAP-TLS (TKIP/AES) • EAP-TTLS (TKIP/AES)  <b>Wireless direct mode:</b> WPA2-PSK (AES)

<b>Mobile OS support</b>	Android 4.0.3 or later iOS® 7 or later (requires 3 <sup>rd</sup> party app development using Brother SDK)
<b>Printer commands</b>	Further information available at <a href="http://www.brother.co.jp/eng/dev/">www.brother.co.jp/eng/dev/</a>  Raster ESC/P P-touch Template ZPL II emulation CPCL emulation
<b>Operating system support</b>	Microsoft® Windows® 7 / Windows® 8 / Windows® 8.1 / Windows® 10  Microsoft® Windows® Server 2008 / Server 2008R2 / Server 2012 / Server 2012R2 / Server 2016 / Server 2019^  Linux
<b>Software</b>	<b>P-touch Editor:</b> Barcode label design software  <b>Brother Print Service Plugin:</b> Driverless printing from Android devices (version 5.0 and above)  <b>Mobile Deploy App:</b> remote printer configuration  <b>Brother Font Manager:</b> font download tool (Windows® only via USB)  <b>Printer Settings Tool:</b> device configuration software (Windows® only via USB)
<b>Internal fonts &amp; sizes</b>	<ESC/P> Bitmap font: Gothic, Letter Gothic Bold, Helsinki Font sizes <16, 24, 32dot> Outline font: Gothic, Letter Gothic Bold, Helsinki, Brussels Font size 400dot (max)  <P-touch Template> Outline font: Gothic, Letter Gothic Bold, Helsinki Font size 400dot (max)  Downloadable font support** via Font Manager software

## Environmental

<b>Drop Protection</b>	2.1m (Under Brother standard environment)
<b>Operating Temperature</b>	Battery -20°C to 55°C AC adapter -10°C to 40°C Car adapter -10°C to 50°C
<b>Operating Humidity</b>	10% to 90% non-condensing
<b>Charging Temperature</b>	0°C to 40°C
<b>Storage Temperature</b>	-20°C to 60° C
<b>Storage Humidity</b>	10% to 90% non-condensing

## Supplies

<b>RD roll type</b>	<b>RD-M01E5:</b> Receipt – 102mm x 27.7m
	<b>RD-M03E1:</b> 72 Labels – 102mm x 152mm
	<b>RD-R03E5:</b> Receipt – 58mm x 12m

## Optional Accessories

<b>Battery</b>	<b>PA-BT-006:</b> Rechargeable Li-ion Smart battery 7.2V continuously printing 10,000 labels (*under Brother standard environment)
<b>Shoulder Strap</b>	PA-SS-4000
<b>Power Options</b>	PA-CR-002A Single Cradle/Charger PA-BC-003 Single Battery Charger PA-AD-600A AC Adapter PA-CD-600CG Cigarette lighter plug PA-CD-600WR Permanently wired PA-BEK-001CG Battery eliminator kit (cigarette lighter plug – 12-48V) PA-BEK-001WR Battery eliminator kit (permanently wired – 12-48V)

\*Connected by USB with new battery and full charge. Printed by Brother specified data (7% coverage 102mm x 29mm) at 23° C.

\*\*Font Licensee permissions are required.

^ RJ-4250WB model only

All specifications are correct at the time of printing and are subject to change without notice. Brother and the brother logo are both trademarks of Brother Industries, Ltd., registered in Japan and certain other countries. Any trade names, logos and product names of other companies appearing are trade names or trademarks of those respective companies.

BIE Product Planning: Last updated 27/01/2021